

Notified body No.1121

Certificate of constancy of performance
1121-CPR-BB5008

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

**“Non-Com Exterior FR Western Red Cedar Euro Class B:
12mm and above”**

Intended use: Solid wood panelling and cladding

Product Performance

Essential characteristics	Performance	Harmonized technical specification
Safety in case of Fire, Reaction to fire	B-s ₂ -d ₀	EN 14915:2013 (Classification report No: 199758)

Product Specification (See Page 3)

Certificate of constancy of performance

1121-CPR-BB5008

Produced for

International Timber

West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ

and produced in the manufacturing plant(s)

West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ

London Road, Purfleet, Essex, RM19 1RE

Earls Road, Grangemouth, Stirlingshire, FK3 8UU

Parkend, Lydney, Gloucestershire, GL15 4JF

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 14915:2013

under system 1 of AVCP are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on **19/05/14** and revised on **15/09/17** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Valid to: 14/09/2020



Paul Duggan
Certification Manager



Exova (UK) Limited trading as Warrington Certification
Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK

Certificate of constancy of performance

1121-CPR-BB5008

Product Specification

General description	Fire retardant western red cedar
Trade name	Non Com
Thickness	12mm and above
Density	229-583 kg/m ³
Flame retardant trade name	Dricon
Net chemical retention	See Note 1 below
Cycle details	See Note 1 below
Brief description of manufacturing process	Pressure impregnation

Note 1: The sponsor of the test has provided this information but at the specific request of the sponsor, this information has been omitted from the test report and is instead held on the confidential file relating to this investigation.

----- End of Certificate -----