

Notified body No. 1121

## Certificate of constancy of performance

### 1121-CPR-BB5004

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

### “Essgee Fireply (Type D1) ATP FR Euro Class C: 3.6mm to 25mm”

**Intended use:** Wood Based Panels

#### Product Performance

Essential characteristics	Performance	Harmonized technical specification
Safety in case of Fire, Reaction to fire	C-s <sub>2</sub> -d <sub>0</sub>	EN 13986:2004 (Classification report No: 139864)

**Product Specification (See Page 3)**

**Certificate of constancy of performance**

**1121-CPR-BB5004**

Produced for

**International Timber**

**West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ**

and produced in the manufacturing plants

**West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ**

**London Road, Purfleet, Essex, RM19 1RE**

**Earls Road, Grangemouth, Stirlingshire, FK3 8UU**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

**EN 13986:2004**

under system 1 of AVCP are applied and that

***the product fulfils all the prescribed requirements set out above.***

This certificate was first issued on **19/05/14** and revised on **10/09/18** and will remain valid to the date given below as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Valid to: **5/03/21**



Paul Duggan  
Certification Manager

**Exova (UK) Limited trading as Warrington Certification  
Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK**



## Certificate of constancy of performance

**1121-CPR-BB5004**

### Product Specification

General description	Essgee Fireply ATP FRC Hardwood plywood
Trade name	"Essgee Fireply (Type D1) ATP FR Euro Class C"
Thickness	3.6mm-25mm
Density	600kg/m <sup>3</sup>
Flame retardant trade name	ATP
Net chemical retention	<b>See Note 1 below</b>
Cycle details	<b>See Note 1 below</b>
Brief description of manufacturing process	Pressure impregnation

**Note 1: The sponsor of the test has provided this information but at the specific request of the sponsor, this information has been omitted from the test report and is instead held on the confidential file relating to this investigation.**

----- End of Certificate -----