



HARDWOOD PLYWOOD DOOR BLANKS

INTRODUCTION:-

Manufactured from both light weight low density plantation hardwoods and a selected wood chip mix.

PROPERTIES

PHYSICAL/STRUCTURAL PROPERTIES All blanks conform to BS 476:Part 22 1987. Flamebreak approximate weight of 31 kg per 2135 x 915 blank - Pacifire Litewood less than 28kg per 2135 x 915 blank. Egger Eurospan have the BM Trada certification for Q-Mark Fire Doors

TYPICAL APPLICATIONS Lightweight firecheck door blanks for conversion into doorsets. Eurospan door cores form an integral component in a door's front line fire protection

ORIGIN Indonesia/Austria

DURABILITY EN 636-2 (Flamebreak)

PURCHASING CYCLE Three monthly

ENVIRONMENTAL CREDENTIALS FSC available and SVLK (Timber Legality Verification System)

STORAGE ADVICE Store in clean, dry conditions where the ambient conditions are similar to that intended for further production and free from excess moisture and changes in humidity and temperature. Store doors perfectly flat on level supports the full width of the door. One support across the centre and one 300mm from each end. Bottom support to be covered with cardboard to prevent marking the doors

FLAMEBREAK DOOR BLANKS			
Product	Code	Stocked	Environmental Credentials
FD30 2135 x 915 x 44mm	DBLK4573	Y	SVLK
FD30 2440 x 1220 x 44mm	DBLK4584	Y	SVLK
FD60 2135 x 915 x 54mm	DBLK5473	Y	SVLK
FSC FD30 2135 x 915 x 44mm	DBLK6073	Y	FSC
Pacifire Litewood FD30			
2135 x 915 x 44mm Falcata Faces	☞	Y	SVLK / FSC
2135 x 915 x 44mm MDF Faces	☞	Y	SVLK / FSC
2440 x 1220 x 44mm Falcata Faces	☞	Y	SVLK / FSC
2135 x 915 x 54mm Falcata Faces	☞	Y	SVLK / FSC
Egger Eurospan FD30			
2060 x 840 x 44mm	☞	Y	FSC
2135 x 915 x 44mm	☞	Y	FSC
2440 x 915 x 44mm	☞	Y	FSC
2440 x 1220 x 44mm	☞	Y	FSC
2800 x 915 x 44mm	☞	Y	FSC

Additional specifications, sizes, chain of custody and specials are available to order All of our stock has been tested by Chiltern International Fire Ltd to BS 476 Part 22.

Further technical information see pages 279 - 282



JOUBERT
force

JOUBERT ALUDOOR



100% Okoume throughout panel with selected plies of Joubert quality mark with two 0.3 mm aluminium cores. The Joubert aludoor panel, available in 40mm and 54mm, is designed for door manufacturing. The aluminium sheet acts as a barrier to humidity, gives better stability and avoids excessive distortion of the panel.



HARDWOOD PLYWOOD DOOR BLANKS



Egger fire door cores are suitable for a wide range of domestic and commercial applications including housing, education and healthcare, hotel and leisure, commercial offices and retail environments.



Pacifire™ doorblanks are available with a variety of surface finishes. Long grain veneers for painting or veneering, MDF/HDF and RedayPaint MDO. Also they can be overlaid with a selection of surfaces using the bespoke CPL service.